

Serial No.: 10/657,856

Listing of Claims:

1. (previously cancelled)
2. (previously cancelled)
3. (previously presented) An apparatus for locking a plug, the apparatus for use with a plug and a plug signal receptacle, the apparatus for locking a plug comprising:
 - a. a plug lock rotatably secured about a first selected point, the plug lock rotates about the first selected point as the plug enters the plug signal receptacle;
 - b. a plug lock spring, the plug lock communicating with the plug lock spring such that the plug lock spring applies force on the plug lock such that the plug lock returns to a neutral position after the plug is fully engaged in the plug signal receptacle;
 - c. a locking release mechanism, the locking release mechanism rotatably secured about a second selected point and a third selected point, the locking release mechanism communicates with the plug lock such that when the plug lock rotates about the first selected point the locking release mechanism rotates about the second selected point and the third selected point;
 - d. a plug lock locking mechanism, the plug lock locking mechanism communicates with the locking release mechanism such that when the locking release mechanism rotates about the second selected point and the third selected point the plug lock locking mechanism secures the plug lock in the neutral position, and the plug lock then retains and holds the plug securely in the plug signal receptacle; and
 - e. an electromagnet, the electromagnet electromagnetically communicating with the plug lock locking mechanism such that when the electromagnet is activated the plug lock no longer retains and holds the plug securely in the plug signal receptacle.
4. (previously cancelled)

5. (previously presented) An apparatus for locking an audio headphone plug, the apparatus for use with a headphone, a headphone plug, and an audio signal receptacle, the apparatus for locking an audio headphone plug comprising:

- a. a plug lock rotatably secured about a first selected axis, the plug lock rotates about the first selected axis as the headphone plug enters the audio signal receptacle;
- b. a plug lock spring, the plug lock communicating with the plug lock spring such that the plug lock spring applies force on the plug lock such that the plug lock returns to a neutral position after the headphone plug is fully engaged in the audio signal receptacle, the neutral position being the plug lock is substantially perpendicular to the audio signal receptacle;
- c. a locking release mechanism, the locking release mechanism rotatably secured about a second selected axis and, the locking release mechanism communicates with the plug lock such that when the plug lock rotates about the first selected axis the locking release mechanism rotates about the second selected axis and the third selected axis;
- d. a plug lock locking mechanism, the plug lock locking mechanism communicates with the locking release mechanism such that when the locking release mechanism rotates about the second selected axis and the third selected axis the plug lock locking mechanism secures the plug lock in the neutral position, and the plug lock then retains and holds the headphone plug securely in the audio signal receptacle; and
- e. an electromagnet, the electromagnet electromagnetically communicating with the plug lock locking mechanism such then when the electromagnet is activated the plug lock no longer retains and holds the headphone plug securely in the audio signal receptacle.

6. (cancelled)

7. (previously presented) An apparatus for locking an audio headphone plug, the apparatus for use with a headphone, a headphone plug, and an audio signal receptacle, the apparatus for locking an audio headphone plug comprising:

- a. a plug lock rotatably secured about a first selected axis, the plug lock rotates about the first selected axis as the headphone plug enters the audio signal receptacle;

b. a plug lock spring, the plug lock communicating with the plug lock spring such that the plug lock spring applies force on the plug lock such that the plug lock returns to a neutral position after the headphone plug is fully engaged in the audio signal receptacle, the neutral position being the plug lock is substantially perpendicular to the audio signal receptacle;

c. a locking release mechanism, the locking release mechanism rotatably secured about a second selected axis and a third selected axis, the locking release mechanism communicates with the plug lock such that when the plug lock rotates about the first selected axis the locking release mechanism rotates about the second selected axis and the third selected axis, the locking release mechanism comprises a plug lock arm, a locking release mechanism arm, a locking release mechanism main member, and a locking release mechanism spring, the plug lock arm and the locking release mechanism arm are pivotally attached to the locking release mechanism main member, the locking release mechanism spring communicating with the locking release mechanism arm;

d. a plug lock locking mechanism, the plug lock locking mechanism communicates with the locking release mechanism such that when the locking release mechanism rotates about the second selected axis and the third selected axis the plug lock locking mechanism secures the plug lock in the neutral position, and the plug lock then retains and holds the headphone plug securely in the audio signal receptacle; and

e. an electromagnet, the electromagnet electromagnetically communicating with the plug lock locking mechanism such then when the electromagnet is activated the plug lock no longer retains and holds the headphone plug securely in the audio signal receptacle.

8. (previously presented) The apparatus for locking an audio headphone plug of claim 7, wherein the apparatus for locking an audio headphone plug further comprises at least two plug locks, at least two plug lock springs and at least two locking release mechanism springs.

9. (original) The apparatus for locking an audio headphone plug of claim 8, wherein the apparatus for locking an audio headphone plug further comprises at least two electromagnets.

10. (currently amended) The apparatus for locking an audio headphone plug of claim 9, wherein the plug lock locking mechanism comprises ~~of~~ a plug lock locking mechanism spring, the total tensile strength of the locking release mechanism springs equals the tensile strength of the plug lock locking mechanism spring.

11. (currently amended) The apparatus for locking an audio headphone plug of claim 10, wherein the total tensile strength of the electromagnets is twice that of the plug lock locking mechanism spring.

Serial No.: 10/657,856

Please amend the specification as follows:

On page 2, lines 12-25:

The instant invention is directed to an apparatus for locking a plug, specifically an apparatus for use with a plug and a plug signal receptacle. The apparatus for locking a plug includes a plug lock, a plug lock spring, a locking release mechanism, and a plug lock locking mechanism. The plug lock is rotatably secured about a first selected point or axis, and the plug lock rotates about the first selected point or axis as the plug enters the plug signal receptacle. The plug lock communicates with the plug lock spring such that the plug lock spring applies force on the plug lock such that the plug lock returns to a neutral position after the plug is fully engaged in the plug signal receptacle. The neutral position being the position where the plug lock is substantially perpendicular to the plug signal receptacle. The locking release mechanism is rotatably secured about a second selected point or axis; the locking release mechanism communicates with the plug lock such that when the plug lock rotates about the first selected point or axis the locking release mechanism rotates about the second selected point or axis. The plug lock locking mechanism communicates with the locking release mechanism such that when the locking release mechanism rotates about the second selected point or axis the plug lock locking mechanism secures the plug lock in the neutral position, and the plug lock then retains and holds the plug securely in the plug signal receptacle.

On page 3, lines 22-26 and page 4, lines 1-9:

The preferred embodiments of the present invention are illustrated by way of example below and in Figures 1-4. The apparatus for locking a plug 1 is for use with a plug 10 and a plug signal receptacle 20 (and/or plug signal receptacle housing 25). Typically, plugs 10 have a substantially circular cross section and the plug signal receptacle 20 has a corresponding shape in order to accept the plug 10. Also, in a typical plug-receptacle configuration when the plug 10 is fully inserted in the plug signal receptacle 20 both the plug 10 and plug signal receptacle 20 are substantially axially aligned. The plugs 10 may be headphone plugs or audio headphone signal plugs 15 attached to a headphone 16, while the plug signal receptacle 20 may be an audio signal receptacle or a headphone plug signal receptacle 21. As seen in Figures 2 and 3, the standard plug 10 typically has a truncated conic section tip 11, with an indentation 12 just past the end of the truncated conic section tip 11. The indentation 12 is typically disposed around the entire cross section of the plug 10. The remaining portion of the plug 10 is typically a shaft 13 and an end portion 14 having a larger cross section than the shaft 13. The end portion 14 and the truncated conic section tip 11 are typically on opposite ends of the shaft 13.

On page 4, line 14-26, and page 5, lines 1-4:

As seen in Figure 1, the apparatus for locking a plug 1 includes a plug lock 100, a plug lock spring 200, a locking release mechanism 300, and a plug lock locking mechanism 400. The plug lock 100 is rotatably secured about a first selected point or

axis 101. In operation, as seen in Figure 2, the plug lock 100 rotates about the first selected point or axis 101 as the plug 10 (or headphone plug 15) enters the plug signal receptacle 20 (or audio signal receptacle 21). The plug lock spring 200 communicates with the plug lock 100 such that the plug lock spring 200 applies force on the plug lock 100 such that the plug lock 100 returns to a neutral position after the plug 10 is fully engaged in the plug signal receptacle 20. The neutral position, as shown in Figures 1, 3 and 4, may be defined, but without limitation, as the position where the plug lock 100 is substantially perpendicular to the plug signal receptacle 20 or the plug 10 itself. The locking release mechanism 300 is rotatably secured about a second selected point or axis 301. The locking release mechanism 300 communicates with the plug lock 100 such that when the plug lock 100 rotates about the first selected point or axis 101 the locking release mechanism 300 rotates about the second selected point or axis 301. The plug lock locking mechanism 400 communicates with the locking release mechanism 300 such that when the locking release mechanism 300 rotates about the second selected point or axis 301 the plug lock locking mechanism 400 secures the plug lock 100 in the neutral position, and the plug lock 100 then retains and holds the plug 10 securely in the plug signal receptacle 20.

On page 5, lines 6-20

As seen in Figures 1-4, the plug lock 100 may include a plug lock boss 105 and a plug lock spring portion 110. The plug lock boss 105 may have first plug lock boss portion 106 and a second plug lock boss portion 107. The first plug lock boss portion

106 may correspond to the indentation 12 of the plug 10. The second plug lock boss portion 107 may have a notch 108 that corresponds to the plug lock locking mechanism 400 and allows the plug lock locking mechanism 400 to lock and secure the first plug lock boss portion 106 in the indentation 12 when the plug 10 is fully inserted in the plug signal receptacle 20. The plug lock spring portion 110 is attached to the second plug lock boss portion 107 on the opposite side of the notch 108. The plug lock spring portion 110 may be rotatably attached to the first selected point or axis 101 and communicates with the plug lock spring 200. As seen in Figure 1, the plug lock boss 105 and the plug lock spring portion 110 may be perpendicular to each other and form a L-shape. The plug lock spring portion 110 may include a first plug lock spring end portion 111 and a second plug lock spring end portion 112. The first plug lock spring end portion 111 may be rounded while the second plug lock spring end portion 112 may be attached to the second plug lock boss portion 107. In the fully inserted position, the plug lock 100 may envelope all or a portion of the indentation 12. The plug lock 100 may also have various detents located throughout the first plug lock boss portion 106.

On page 5, lines 21-26 and page 6, lines 1-14:

As seen in Figure 1, the locking release mechanism 300 may include a plug lock arm 305, a locking release mechanism arm 310, a locking release mechanism main member 315, and a locking release mechanism spring 320. The plug lock arm 305 and the locking release mechanism arm 310 may be located on opposite ends of the locking

release mechanism main member 315. Both the plug lock arm 305 and the locking release mechanism arm 310 may be pivotally attached to the locking release mechanism main member 315. The plug lock arm 305 may include a first plug lock arm end portion 306 and a second plug lock arm end portion 307. The first plug lock arm end portion 306 may have a fluke or have substantially a triangular shape. In the preferred embodiment, as seen in Figure 1, the first plug lock arm end portion 306 communicates with the second plug lock boss portion 107, while the second plug lock arm end portion 307 is pivotally or rotatably attached to the locking release mechanism main member 315. The locking release mechanism arm 310 may include a first locking release mechanism arm end portion 311 and a second locking release mechanism arm end portion 312. In one of the embodiments, as seen in Figure 1, the first locking release mechanism arm end portion 311 communicates with the plug lock locking mechanism 400, while the second locking release mechanism arm end portion 312 is pivotally or rotatably attached to the locking release mechanism main member 315. The locking release mechanism spring 320 may also communicate with the second locking release mechanism arm end portion 312 and/or the locking release mechanism main member 315. As seen in Figures 1 and 2, the first locking release mechanism arm end portion 311 may also rotate about a third selected point or axis 302.

On page 6, lines 21-26 and page 7, lines 1-9:

The plug lock locking mechanism 400 may include a plug lock locking mechanism arm 405, a plug lock locking mechanism base 410 and a plug lock locking mechanism spring 415. The plug lock locking mechanism arm 405 may include a first plug lock locking mechanism arm end portion 406 and a second plug lock locking mechanism arm end portion 407. The first plug lock locking mechanism arm end portion 406 corresponds to the notch 108 in the second plug lock boss portion 107. The second plug lock locking mechanism arm end portion 407 is attached to the plug lock locking mechanism base 410. The plug lock locking mechanism base 410 communicates with the plug lock locking mechanism spring 415. The plug lock locking mechanism arm 405 may also include a gain 408. The gain 408 may be larger than the cross section of the first locking release mechanism arm end portion 311. The first locking release mechanism arm end portion 311 or a portion thereof may be disposed within the gain 408. As seen in Figure 1, in the neutral position without a plug 10 fully engaged in the plug signal receptacle 20, the locking release mechanism spring 320 exerts force upon the locking release mechanism arm 310 causing the bottom of the first locking release mechanism arm end portion 311 to press on the lower portion of the gain 408, opposing the force of the plug lock locking mechanism spring 415.

On page 7, lines 22-26 and page 8, lines 1-10:

In operation, in the preferred embodiment, as seen in Figure 2, when the plug 10 enters the plug signal receptacle 20, the truncated conic section tip 11 presses against the plug lock boss ~~portion~~ 105 which causes the plug lock 100 to rotate or pivot about the

first selected point or axis 101. The second plug lock boss portion 107 presses against the tip of first plug lock arm end portion 306, causing the plug lock arm 305 and the locking release mechanism arm 310 to rotate or pivot about the second selected point or axis 301 and the third selected point or axis 302. As seen in Figure 3, this then allows the plug lock locking mechanism 400 to go upward due to the plug lock locking mechanism spring 415 and the bottom of the first locking release mechanism arm end portion 311 no longer pressing on the lower portion of the gain 408, and opposing the force of the plug lock locking mechanism spring 415. As the plug 10 is fully engaged, the plug lock spring 200 then pushes the first plug lock boss portion 106 into the indentation 12. At or about the same time the first plug lock locking mechanism arm end portion 406 enters into the notch 108 locking the plug 10 into the plug signal receptacle 20. In order to unlock the plug 10 from the plug signal receptacle 20 the electromagnets 500 are activated, and then the electromagnets 500 pull the first plug lock locking mechanism arm end portion 406 away from the notch 108.